

IN THE SPECIFICATION:

Please rewrite page 10 as follows:

--the openings 104, 106. When the supporting member 108 is in the first position, the holder 100 may be retracted into a rectangular pocket (not shown). When the holder 100 is withdrawn from the pocket, the supporting member 108 may be rotated to the second position so that beverage containers placed into the square openings 104, 106 of the tray portion are supported from beneath by the supporting member 108. The supporting member 108 is preferably spring loaded, e.g. by spring 110 so that it automatically rotates to the second position when the holder is withdrawn from the pocket. As with the ^{first} ~~first~~ embodiment, this embodiment includes a plurality of resilient inwardly extending fingers 112, 114, 116, 118, 120, 122, 124, 126, each of which assumes a generally V-shaped configuration when viewed in a vertical plane. The fingers are arranged inside the square openings 104, 106 and extend approximately one half inch inward. According to a presently preferred second embodiment, the tray portion is approximately 6.5 x 6.5 x 0.875 inches and has front and rear flanges 130, 132 which depend downward approximately 1.5 inches. The purpose of the flanges is to limit movement of the holder 100 into and out of the pocket (not shown). The square openings 104, 106 are each 2.875 inches square and are spaced approximately 0.5 inches apart. The rotating support member 108 depends approximately 3 inches from the--
